



HALAR (ECTFE) & KYNAR (PVDF) CATHODIC PROTECTION CABLE

Annealed stranded bare copper conforming to ASTM B-8 with an insulated wall of PVDF or ECTFE over the bare conductor. A high molecular weight polyethylene (HMWPE) jacket insulation conforming to ASTM D 1248 is extruded over the PVDF/ECTFE.



USED IN CATHODIC PROTECTION SYSTEMS FOR:

- Pipelines
- Oil Tanks
- Steel Pipe
- Well Casings
- Underground or Submerged Metallic Objects/Structures

FEATURES:

- Custom Print Available
- Direct Burial
- Abrasion Resistant
- Crush Resistant
- Oil Resistant
- Sunlight Resistant

<i>Product Specifications</i>	8 AWG	6 AWG	4 AWG	2 AWG
<i>Stranding</i>	7 /0.0486"	7/0.0612"	7/0.0772"	7/0.0974"
<i>Diameter</i>	0.146	0.184	0.232	0.292
<i>Operating Temperature</i>	75°C	75°C	75°C	75°C
<i>Insulation Thickness</i>	0.020	0.020	0.020	0.020
<i>Jacket Thickness</i>	0.065	0.065	0.065	0.065
<i>Diameter</i>	0.316	0.354	0.402	0.462
<i>Weight Per 1,000'</i>	81	116	170	254
<i>Operating Voltage</i>	600V	600V	600V	600V